

Amendment No. 149

Senate Amendment to Senate Bill No. 251

(BDR 43-463)

Proposed by: Committee on Transportation and Homeland Security**Amendment Box:****Resolves Conflicts with:** N/A**Amends:** Summary: No Title: No Preamble: No Joint Sponsorship: No Digest: Yes

ASSEMBLY ACTION	Initial and Date	SENATE ACTION	Initial and Date
Adopted <input type="checkbox"/> Lost <input type="checkbox"/>	_____	Adopted <input type="checkbox"/> Lost <input type="checkbox"/>	_____
Concurred In <input type="checkbox"/> Not <input type="checkbox"/>	_____	Concurred In <input type="checkbox"/> Not <input type="checkbox"/>	_____
Receded <input type="checkbox"/> Not <input type="checkbox"/>	_____	Receded <input type="checkbox"/> Not <input type="checkbox"/>	_____

Amend section 1, page 2, by deleting lines 10 through 12 and inserting:

“2. If the motor vehicle was not manufactured to include a bracket, device or other contrivance to display and secure a front license plate, and if the manufacturer of the motor vehicle provided no other means or method by which a front license plate may be displayed upon and secured to the motor vehicle:”.

MSM/BJE

Date: 4/4/2005

S.B. No. 251—Authorizes operation of certain motor vehicles without front license plate under certain circumstances.

**If this amendment is adopted, the Legislative
Counsel's Digest will be changed to read as follows:**

Legislative Counsel's Digest:

Existing law provides that, with the exception of motorcycles, power cycles and motor vehicles being transported by a licensed vehicle transporter, a motor vehicle must have two license plates attached thereto, one in the front and one in the rear. (NRS 482.275)

This bill provides that if a motor vehicle would otherwise be required to have two license plates attached thereto, but: (1) the motor vehicle was not manufactured to include a bracket, device or other contrivance for displaying and securing a front license plate; and (2) the manufacturer of the motor vehicle provided no other means or method for displaying and securing a front license plate, the motor vehicle must have one license plate attached in the rear and the other license plate may be, but is not required to be, attached in the front.